



Product information

XTC TURBO 15W40

Bardahl XTC TURBO 15W40 Motor Oil has been developed for the lubrication of modern petrol and diesel engines with or without turbo-chargers. This oil is highly resistant to extremely high temperatures, such as occur in turbo-chargers. It prevents the formation of combustion residues on the turbo-bearings. It is designed to meet the most modern low emission diesel engines.

Bardahl XTC TURBO 15W40 Motor Oil is composed of high-grade solvent refined base oils with balanced additives. The purpose of the anti-wear and anti-oxidation additives is to lubricate and protect an engine under the most widely divergent circumstances. It provides outstanding protection and exceeds the performance requirements of all diesel and petrol engine manufacturers.

Bardahl XTC TURBO 15W40 Motor Oil is designed to promote long engine life under the most demanding conditions and is used by large commercial and industrial fleets. This oil is designed to meet the most demanding requirements for engine cleanliness and high and low temperature deposit control.

This universal oil, also called **multifleetoil**, has several important properties.

1. Protection against wear, corrosion and foaming.
2. No sludge formation because of good dispersive power.
3. High and stable viscosity index.
4. A good detergency prevents deposits in hot areas of the engine.
5. A low sulfated ash number.

Direction for use

This oil complies with the strictest requirements of petrol engines as well as LPG engines and diesel engines, with or without turbo-charger. May also be used when a lower specification is required, such as e.g. SH, SG and CE.

A trade universal oil recommended for use in over-the-road diesel trucks, heavy duty construction equipment, mixing equipment, farm vehicles, oil-field engines, diesel passenger cars and petrol engines.

Specifications

API SL/CF
ACEA A3/ B4-08
ACEA A3/ B3-10
Mercedes Benz 229.1
VW 501.01, 505.00

BARDAHL NL 6 OCD INTERNATIONAL

Maxwellstraat 41 - 2216GP Dordrecht - Postbus 9024 - 3301 AA Dordrecht

Tel (078) 6512322 - Fax (078) 6174848 - email: info@bardahl.nl - website: www.bardahl.nl

GB50100



Product information

Analytical-data

Viscosity: mm ² at 100°C	14.5
Viscosity: mm ² at 40°C	110
Viscosity Index	137
Viscosity: mpa/s at	-15°C
	3300
Sulphated Ash: wt.%	1.03
TAN: mg KOH/g ASTM D664	2.2
TBN: mg KOH/g ASTM D2896	8.4
Pourpoint: °C	-36
Flashpoint: COC: °C	220
Specific Gravity at 15/15°C	0.885
Noack Evaporation: wt.%	13.5

The above figures are typical analyses data and should not be used as specifications.

Article number 50151
Contents 1 liter

Article number 50155
Contents 5 liter

Article number 50182
Contents 25 liter

Article number 50186
Contents 60 liter

Article number 50192
Contents 210 liter