



Product information

Ceramic Paste

Bardahl Ceramic Paste is a release and mounting paste. It is a balanced combination of very fine ceramic parts, a non-melting grease and special anti-corrosion and anti-oxidation inhibitors. **Bardahl Ceramic Paste** is metal free.

Advantages

- Rapidly and easy mounting of wire connections.
- Prevents corrosion
- Gives a quick and easy release of bolt/nut connections, even after exposure to high temperatures with peaks up to 1200°C, corrosive atmospheres or extreme pressures.
- Reduces wear on places with high friction.
- Will prevent corrosion by acids, salt or caustics.
- Will not be washed away by water.

Applications

The ceramic parts of **Bardahl Ceramic Paste** will fill the irregularity on the surface. The available film will not cure, lump or melt and will not break down by trembling, shrinkage or expansion. During the use, for example when tightening a bolt, the surface will be honed by the ceramic parts. Because of this a strongly adhered film on the treated metals will arise. At the same time the treated parts will be cut off from the atmosphere.

Analytical-data

Color	:	grey
N.L.G.I. number	:	2
Dropping point	:	none
Copper corrosion (IP 112)	:	good
Working temperature, °C	:	-40 till +1200
Melting temperature ceramic, °C	:	3000
Viscosity base oil, cSt	:	
at 40°C	:	210
at 100°C	:	18,5
Flash point base oil, °C	:	270

Article number 76501
Contents 100 gr

Article number 76502 (pressure pack)
Contents 200 ml

Article number 76504
Contents 400 ml (spray)

BARDAHL NL 6 OCD INTERNATIONAL

Maxwellstraat 41 - 2216GP Dordrecht - Postbus 9024 - 3301 AA Dordrecht

Tel (078) 6512322 - Fax (078) 6174848 - email: info@bardahl.nl - website: www.bardahl.nl

GB76500



Product information

Article number 76505
Contents 500 gr

Article number 76582
Contents 20 kg

Article number 76586
Contents 50 kg