

## Special Gear Oil 75W80 GL<sup>4+</sup>

**Bardahl Special Gear Oil 75W80** is an EP (high-pressure) lubricating oil for gear transmissions, especially to meet the toughest requirements, i.e.: high speeds, shocks and high torque at low revs. This lubricating oil has a special additive package that ensures:

- very good EP properties
- excellent oxidation stability
- very liquid at low temperatures
- very high and stable viscosity index
- a strong anti-wear, anti-foam and anti-corrosion ability

### Applications

**Bardahl Special Gear Oil 75W80** is recommended for all hypoid transmissions and is also ideal for conical transmissions with helicoital toothing, for worm boxes and most of the gearboxes.

### Specifications

— API GL-4 +	— HONDA MTF 94	— SUBARU K0321-F0090
— BMW 83220309031	— HYUNDAI 02200-00130 TOD	— TOYOTA JWS 227
— BMW MTF LT-2	— LAND ROVER TYK500030	— VOLVO 97308
— FIAT 9.55550-MX3	— MB 235.10	— VOLVO 97309
— FIAT 9.55550-MZ1	— MITSUBISHI MZ312644	— VOLVO 97310
— FORD WSS-M2C200-D2	— NISSAN 999MP-MTF20P	— VW G 052 171
— FORD ESD-M2C186-A	— NISSAN MT-XZ	— VW G 052 726
— GM 1940182	— PSA B71 2330	— VW G 052 527
— GM 1940768	— PSA 9730 A2	— VW G 055 538
	— PSA 9730 A8	

### Analysis of data

Test			Results
SAE - Class	Method	Unit	Special Gear Oil 75W80 GL4
Viscosity; cst at 100°C	ASTM D445	Cst	8,0
Viscosity; cst at 40°C	ASTM D445	Cst	42
Viscosity Index	ASTM D2270		165
Pour point;°C	ASTM D6892	°C	-45
Flashpoint; COC;°C	ASTM D92	°C	190
Specific Gravity at 15/15°C	ASTM D4052	g/ml	0,880



**Article number** 52251  
**Contents** 1 liter

**Article number** 52255  
**Contents** 5 liter

**Article number** 52282  
**Contents** 25 liter

**Article number** 52286  
**Contents** 60 liter

**Article number** 52292  
**Capacity** 210 litres