

Special Gear Oil 75W80 GL⁴⁺

Bardahl Special Gear Oil 75W80 is an EP (high-pressure) lubricating oil for gear transmissions, especially to meet the toughest requirements, i.e.: high speeds, shocks and high torque at low revs. This lubricating oil has a special additive package that ensures:

- very good EP properties
- excellent oxidation stability
- very liquid at low temperatures
- very high and stable viscosity index
- a strong anti-wear, anti-foam and anti-corrosion ability

Applications

Bardahl Special Gear Oil 75W80 is recommended for all hypoid transmissions and is also ideal for conical transmissions with helicoital toothing, for worm boxes and most of the gearboxes.

Specifications

API - GL-4 | BMW - 83 22 0 140 516 | BMW - 83220309031 | BMW - MTF LT-2 | FIAT - 9.55550-MX3 | FIAT - 9.55550-MZ1 | FORD - ESD-M2C186-A | FORD - WSS-M2C200-D2 | GM - 1940182 | GM - 1940768 | HONDA - MTF 94 | HYUNDAI - 02200-00130 TOD | LAND ROVER - TYK500030 | MB - 235.10 | MITSUBISHI - MZ312644 | NISSAN - 999MP-MTF20P | NISSAN - MT-XZ | PSA - 9730 A2 | PSA - 9730 A8 | PSA - B71 2330 | SUBARU - K0321-F0090 | TOYOTA - JWS 227 | VOLVO - 97308 | VOLVO - 97309 | VOLVO - 97310 | VW - G 052 171 | VW - G 052 527 | VW - G 052 726 | VW - G 055 538

Analysis of data

Test			Results
SAE - Class	Method	Unit	Special Gear Oil 75W80 GL4
Viscosity; cst at 100°C	ASTM D445	Cst	8,0
Viscosity; cst at 40°C	ASTM D445	Cst	42
Viscosity Index	ASTM D2270		165
Pour point;°C	ASTM D6892	°C	-45
Flashpoint; COC;°C	ASTM D92	°C	190
Specific Gravity at 15/15°C	ASTM D4052	g/ml	0,880

Article number 52251
Contents 1 liter

Article number 52255
Contents 5 liter

Article number 52282
Contents 25 liter

Article number 52286
Contents 60 liter



Article number 52292
Capacity 210 litres