

XTG Gear Oil 75W140 GL5 LS Syntronic

Bardahl Gear Oil 75W140 GL5 is a high-quality synthetic transmission oil for all limited slip differentials, including those equipped with a limited slip differential.

Properties

- A very high viscosity index that makes the oil temperature stable
- Highly liquid at low temperatures
- Excellent resistance to aging and deposition.
- "Limited-slip" characteristics

Application

Bardahl Gear Oil 75W140 GL5 is recommended for 4x4 vehicles.

Specifications

API - GL-5 | MIL - L-2105 C | MIL - L-2105 D | BMW - 83 22 1 470 080 | BMW - 83 22 2 282 583 | BMW - MSP/A | FORD - WSS-M2C187-A | FORD - WSS-M2C192-A | FORD - WSS-M2C192A+/M2C118-A | GM - 12346140 | GM - 1942386

Analysis data

Test			Results
SAE - Class	Method	Unit	XTG Gear Oil 75W140 GL5
Density at 15 °C	ASTM D4052	g/ml	0.905
Viscosity 40 °C	ASTM D445	Cst	170
Viscosity 100 °C	ASTM D445	Cst	26,5
Viscosity at -40 °C	ASTM D2983	mPa.s	142.000
Viscosity index	ASTM D2270		195
Flashpoint	ASTM D92	°C	205
Pour point	ASTM D6892	°C	-45

Article number 59151

Contents 1 liter

Article number 59155

Contents 5 liter

Article number 59182

Contents 25 liter

Article number 59186

Contents 60 liter

Article number 59192

Contents 210 liter