

## Universal Shipping Grease

**Bardahl Universal Shipping Grease** is a newly developed grease mainly for lubrication & sealing of propeller shafts. It is focused on this lubrication but can also be used very well on board as a grease for sliding and ball bearings, so that the Multi-purpose character comes into its own.

This grease can also be used for general use such as chassis lubrication and other lubrication points where a tough and long-lasting lubrication film is required.

### Advantages

---

- Very good anti-corrosion properties
- More than enough EP properties
- Good antioxidant properties
- Excellent resistance to fresh and salt water
- Good adhesion properties
- Easily pumpable in automatic grease lubricators
- High mechanical stability
- Does not affect rubber

### Analysis data

Test	Results
Colour	Brown
Thickener	Lithium – calcium
Base oil nature	Mineral
Unworked penetration at 25°C	245 - 270
Drop point, °C	Min. 180
Welding load, kg	Min. 300
Oxidation stability 100°C, bar	(Hofmann ) Max. 0,5
Corrosion EMCOR	Grade 1
Copper corrosion, 24h/100°C	Max. 1b
Water wash out, 80°C, (%)	Max. 2
Temperature Range, (°C)	-25 to 120

**Article number** 74304

**Content** 400 gr

**Article number** 74305

**Content** 500 gr

**Article number** 74351

**Content** 1 kg

**Article number** 74355

**Content** 5 kg

**Article number** 74382

**Content** 20 kg