

Diesel Antifreeze

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
Issue date: 8/31/2020 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Name : Diesel Antifreeze
Product code : 025
Article number : 02500

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : Consumer use
Professional use.
Function or use category : Fuel additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

No additional information available

1.4. Emergency telephone number

Country	Official advisory body	Address	Emergency number	Comment
	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	0870 243 2241	
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
Israel	Israel Poison Information Center Rambam Health Care Campus	6 Ha'Aliya Street 31096 Haifa	+972 4 854 1900	
Malta	Medicines & Poisons Info Office	Mater Dei Hospital MSD Msida	+356 2545 6504	
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH Birmingham	0344 892 0111	
United Kingdom	National Poisons Information Service (Belfast Centre) Royal Victoria Hospital	Grosvenor Road BT12 6BA Belfast	0344 892 0111	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3 H226
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation H335
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336
Aspiration hazard, Category 1 H304
Hazardous to the aquatic environment — Chronic Hazard, Category 2 H411

Diesel Antifreeze

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

May be harmful in contact with skin. Toxic to aquatic life.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS02

GHS07

GHS08

GHS09

Signal word (CLP)

: Danger

Contains

: Hydrocarbons, C9, aromatics; Solvent naphtha (petroleum), heavy aromatic

Hazard statements (CLP)

: H226 - Flammable liquid and vapour.

H304 - May be fatal if swallowed and enters airways.

H335 - May cause respiratory irritation.

H336 - May cause drowsiness or dizziness.

H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P331 - Do NOT induce vomiting.

P370+P378 - In case of fire: Use dry sodium carbonate for extinction.

P210 - Keep away from heat, sparks, open flames, hot surfaces. — No smoking.

P273 - Avoid release to the environment.

P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P501 - Dispose of contents/container an approved waste disposal plant.

EUH-statements

: EUH066 - Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

Other hazards.

: May be harmful in contact with skin. Toxic to aquatic life. May be harmful if swallowed.
Causes mild skin irritation.

PBT: not relevant – no registration required

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C9, aromatics	(EC-No.) 918-668-5 (REACH-no) 01-2119455851-35	50 – 100	Flam. Liq. 3, H226 STOT SE 3, H335 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Solvent naphtha (petroleum), heavy aromatic	(CAS-No.) 64742-94-5 (EC-No.) 265-198-5 (EC Index-No.) 649-424-00-3 (REACH-no) 01-2119463588-24	5 – 10	Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Full text of H-statements: see section 16

Diesel Antifreeze

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Seek medical attention immediately.
First-aid measures after inhalation	: Obtain emergency medical attention. Allow affected person to breathe fresh air.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Rub greasy cream into the skin.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Drink plenty of water. Never give anything by mouth to an unconscious person. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Respiratory complaints. May cause drowsiness or dizziness. Prolonged or repeated contact may cause skin to become dry or cracked. Irritating to respiratory system.
------------------	---

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Aspiration hazard. Keep the victim warm. Allow the victim to rest.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry chemical. Carbon dioxide. Water haze. Move containers from fire area if it can be done without personal risk.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapour.
Explosion hazard	: May form flammable/explosive vapour-air mixture. Vapors can spread and a blowtorch to return itself to an ignition source. Vapor explosion indoors, outdoors or in sewers. The substances are marked with a "P" may polymerize explosively when they are heated or get involved in a fire. Runoff to sewer may create fire or explosion hazard. The substance can be transported in a hot state. Keep product and empty containers away from heat and ignition sources. Prevent product from entering drains. Very toxic to aquatic life with long lasting effects.
Hazardous decomposition products in case of fire	: Carbon dioxide. Carbon monoxide. Nitrogen oxides.

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection. Do not breathe gas, fumes, vapour or spray.
Other information	: Prevent fire fighting water from entering the environment. Toxic to aquatic organisms.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: May be dangerously slippery if spilled. Keep public away from danger area. Spray with water to reduce vapours.
------------------	--

6.1.1. For non-emergency personnel

Emergency procedures	: Evacuate unnecessary personnel.
----------------------	-----------------------------------

6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection. Do not breathe gas/fumes/vapour/spray.
Emergency procedures	: Ventilate area. Keep away from sources of ignition - No smoking. Use special care to avoid static electric charges.

Diesel Antifreeze

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

6.2. Environmental precautions

Stop leak if safe to do so. Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Dike the product for recovery.
Methods for cleaning up	: Soak up with inert absorbent material (for example sand, sawdust, a universal binder, silica gel). Use suitable disposal containers. Place spillage in an appropriate labeled container for disposal. Clean contaminated surface thoroughly.
Other information	: Wear suitable protective clothing. Prevent product from entering drains. Take precautionary measures against static discharge.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". Ecological information (Section 12).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Ensure adequate ventilation, especially in confined areas. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharges. Use only non-sparking tools. Use grounded electrical/mechanical equipment. Provide local exhaust or general room ventilation. Wear suitable protective clothing. Do not breathe gas, fumes, vapour or spray. Notify authorities if product enters sewers or public waters. Avoid contact with skin, eyes and clothing.
Hygiene measures	: Do not eat, drink or smoke when using this product. Regular cleaning of equipment, work area and clothing.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: correctly labelled. Store in a well-ventilated place. Keep container tightly closed. Store in original container. Prevent soil and water pollution. Restrict access to stockrooms.
Incompatible materials	: heat. sparks. Open flame. Sources of ignition.
Storage area	: Provide for an automatic sprinkler system. Store in a well-ventilated place.

7.3. Specific end use(s)

This information is provided in the present safety data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Solvent naphtha (petroleum), heavy aromatic (64742-94-5)

EU - Occupational Exposure Limits

IOELV TWA (mg/m ³)	2000 mg/m ³
IOELV TWA (ppm)	500 ppm

8.2. Exposure controls

Appropriate engineering controls:

Provide local exhaust or general room ventilation.

Hand protection:					
Refer to manufacturer's information.					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Safety gloves					EN ISO 374

Diesel Antifreeze

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Eye protection:			
Type	Use	Characteristics	Standard
Safety glasses		With side shields	

Skin and body protection:	
Type	Standard
Wear suitable protective clothing	
antistatic boots	

Respiratory protection:			
In case of insufficient ventilation, wear suitable respiratory equipment			
Device	Filter type	Condition	Standard
Self-contained breathing apparatus (SCBA)	Filtertype: ABEK1/ABEK2		

Environmental exposure controls:

Prevent entry to sewers and public waters.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Yellow.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: > 140 °C
Flash point	: ≈ 40 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Non flammable.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: Water: < 1 %
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

Diesel Antifreeze

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat. Sparks. Open flame. Sources of ignition.

10.5. Incompatible materials

Acids. Bases. Oxidizing agent.

10.6. Hazardous decomposition products

Nitrogen oxides. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified as dangerous according to the criteria of Regulation (EC) No 1272/2008
Acute toxicity (dermal) : Not classified as dangerous according to the criteria of Regulation (EC) No 1272/2008
Acute toxicity (inhalation) : Not classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Hydrocarbons, C9, aromatics

LD50 oral rat	> 2000 mg/kg
LD50 dermal rat	> 2000 mg/kg

Solvent naphtha (petroleum), heavy aromatic (64742-94-5)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5 mg/l/4h

Skin corrosion/irritation : Not classified as dangerous according to the criteria of Regulation (EC) No 1272/2008
Serious eye damage/irritation : Not classified as dangerous according to the criteria of Regulation (EC) No 1272/2008
Respiratory or skin sensitisation : Not classified as dangerous according to the criteria of Regulation (EC) No 1272/2008
Germ cell mutagenicity : Not classified as dangerous according to the criteria of Regulation (EC) No 1272/2008
Carcinogenicity : Not classified as dangerous according to the criteria of Regulation (EC) No 1272/2008
Reproductive toxicity : Not classified as dangerous according to the criteria of Regulation (EC) No 1272/2008
STOT-single exposure : May cause respiratory irritation. May cause drowsiness or dizziness.
STOT-repeated exposure : Not classified as dangerous according to the criteria of Regulation (EC) No 1272/2008
Aspiration hazard : May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute) : Not classified as dangerous according to the criteria of Regulation (EC) No 1272/2008
Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.

Diesel Antifreeze

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hydrocarbons, C9, aromatics	
LC50 fish 1	9.2 mg/l (Oncorhynchus mykiss 96h)
EC50 Daphnia 1	1 – 10 mg/l
EC50 Daphnia 2	3.2 mg/l
ErC50 (algae)	2.9 mg/l (Pseudokirchneriella subcapitata 72h)
NOEC (acute)	1 mg/l (Pseudokirchneriella subcapitata 72h)

Solvent naphtha (petroleum), heavy aromatic (64742-94-5)	
LC50 fish 2	2.34 mg/l (Oncorhynchus mykiss)
EC50 Daphnia 1	0.95 mg/l
EC50 72h algae (2)	2.5 mg/l

12.2. Persistence and degradability

Hydrocarbons, C9, aromatics	
Biodegradation	78 % (672h)

Solvent naphtha (petroleum), heavy aromatic (64742-94-5)	
Persistence and degradability	Not readily biodegradable.

12.3. Bioaccumulative potential

Solvent naphtha (petroleum), heavy aromatic (64742-94-5)	
Partition coefficient n-octanol/water (Log Pow)	2.9 – 6.1
Bioaccumulative potential	bioaccumulative.

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Diesel Antifreeze	
PBT: not relevant – no registration required	

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Additional information	: Recycle after cleaning. Empty the packaging completely prior to disposal. Handle empty containers with care because residual vapours are flammable.
European List of Waste (LoW) code	: Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

Diesel Antifreeze

Safety Data Sheet


according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
UN 1268	UN 1268	UN 1268	UN 1268	UN 1268
14.2. UN proper shipping name				
PETROLEUM DISTILLATES, N.O.S.	PETROLEUM DISTILLATES, N.O.S.	Petroleum distillates, n.o.s.	PETROLEUM DISTILLATES, N.O.S.	PETROLEUM DISTILLATES, N.O.S.
Transport document description				
UN 1268 PETROLEUM DISTILLATES, N.O.S. (Hydrocarbons, C9, aromatics), 3, III, (D/E), ENVIRONMENTALLY HAZARDOUS	UN 1268 PETROLEUM DISTILLATES, N.O.S. (Hydrocarbons, C9, aromatics), 3, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1268 Petroleum distillates, n.o.s. (Hydrocarbons, C9, aromatics), 3, III, ENVIRONMENTALLY HAZARDOUS	UN 1268 PETROLEUM DISTILLATES, N.O.S., 3, III, ENVIRONMENTALLY HAZARDOUS	UN 1268 PETROLEUM DISTILLATES, N.O.S., 3, III, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)				
3	3	3	3	3
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR) : F1
 Special provisions (ADR) : 664
 Limited quantities (ADR) : 5I
 Excepted quantities (ADR) : E1
 Packing instructions (ADR) : P001, IBC03, LP01, R001
 Mixed packing provisions (ADR) : MP19
 Portable tank and bulk container instructions (ADR) : T4
 Portable tank and bulk container special provisions (ADR) : TP1, TP29
 Tank code (ADR) : LGBF
 Vehicle for tank carriage : FL
 Transport category (ADR) : 3
 Special provisions for carriage - Packages (ADR) : V12
 Special provisions for carriage - Operation (ADR) : S2
 Hazard identification number (Kemler No.) : 30
 Orange plates :



Tunnel restriction code (ADR) : D/E
 EAC code : 3YE

Transport by sea

Special provisions (IMDG) : 223, 955
 Limited quantities (IMDG) : 5 L

Diesel Antifreeze

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP29
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-E
Stowage category (IMDG)	: A
Properties and observations (IMDG)	: Immiscible with water.

Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3
ERG code (IATA)	: 3L

Inland waterway transport

Classification code (ADN)	: F1
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 0

Rail transport

Classification code (RID)	: F1
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T4
Portable tank and bulk container special provisions (RID)	: TP1, TP29
Tank codes for RID tanks (RID)	: LGBF
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Colis express (express parcels) (RID)	: CE4
Hazard identification number (RID)	: 30

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

15.1.2. National regulations

France

Occupational diseases : RG 84 - Affections engendrées par les solvants organiques liquides à usage professionnel

Diesel Antifreeze

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Germany

Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG)
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG)

Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1)

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

ABM category : A(2) - toxic for aquatic organisms, may have longterm hazardous effects in aquatic environment

SZW-lijst van kankerverwekkende stoffen : Solvent naphtha (petroleum), heavy aromatic is listed

SZW-lijst van mutagene stoffen : Solvent naphtha (petroleum), heavy aromatic is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

15.2. Chemical safety assessment

No

SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : Abbreviations and acronyms:

RID: Regulations Concerning the International Transport of Dangerous Goods by Rail

ICAO: International Civil Aviation Organization

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent.

Full text of H- and EUH-statements:

Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H335	May cause respiratory irritation.

Diesel Antifreeze

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.