

NAUTIC MOTOR OIL 5W40 Inboard

Bardahl NAUTIC Motor Oil 5W40 Inboard is a fully synthetic 4-stroke motor oil that has been specially developed for both modern gasoline and diesel engines that are subject to extreme requirements. The extensive range of additives, in combination with the best base oil, ensures maximum protection against friction and wear at low and very high temperatures.

Application

Recommended for faster/heavier loaded pleasure craft that need to deliver high performance.

Specifications

API Service SN/CF

Analysis data

Test			Results
SAE - classe	Method	Unit	XTC RS 5W40 Syntronic
Viscosity; Cst at 100°C	ASTM D445	mm ² /s	14.5
Viscosity; Cst at 40°C	ASTM D445	mm ² /s	85
Viscosity index	ASTM D2270		168
Viscosity; Cst -30°C	ASTM D5293	mPa.s	6600
Sulfated Ash	ASTM D874	wt. %	1.20
TAN	ASTM D2896	mg KOH/g	2.5
TBN	ASTM D2896	mg KOH/g	10.5
Pourpoint	ASTM D6892	°C	-51
Flashpoint	ASTM D92	°C	230
Specific Gravity at 15/15°C	ASTM D4052	g/ml	0.850
Noack Evaporation		wt. %	8.2

Article number 48451

Contents 1 liter

Article number 48455

Contents 5 litres

Article number 48482

Contents 25 liter

Article number 48486

Contents 60 litres

Article number 48492

Contents 210 litres