XTC 0W20 Syntronic LL

Bardahl XTC 0W20 Syntronic LL (longlife) is a fully syntheticengineoil,mandatory for the latest engines from VW/Audi. This oil has been developed to create eand clean engine with minimal pollution. Protects against wear, so that the engine remains like new and continues to perform. This lubricating oil has been developed for a maximum service life of emission systems and maximum efficiency. Due to the ultra-low 0W20 viscosity class, a substantial fuel saving is achieved.

Applications

Bardahl XTC 0W20 Syntronic LL has been developed for mandatory use in the new 2.0 TFSI 140 kW and 3.0 TDI CR 160 kW engines from VW and Audi that require vw specifications 508 00 and 509 00.

Characterize

- Fuel savings: contributes to fuel savings and reduction of CO2 emissions.
- Good engine protection: performance in terms of keeping the engine clean.
- Cold start: very good fluidity at low temperatures.

Specifications

- API SN Plus
- ACEA C5
- PORSCHE C20
- VW 508.00/509.00/TL 52 577

Analytical data

Test			Results
SAE - Class	**Method**	**Unit**	**XTC 0W20 Syntronic LL**
Density 15 °C	ASTM D4052	g/ml	0.835
CCS-viscosity at -35 °C,	ASTM D5293	mPa.s	3500
Viscosity at 40 °C	ASTM D445	mm²/s	40.2
Viscosity at 100 °C	ASTM D445	mm²/s	8.2
Viscosity index	ASTM D2270		184
Flashpoint COC, °C	ASTM D92	°C	235
Pour point, °C	ASTM D6892	°C	-51
Total Base Number	ASTM D2896	mg KOH/g	8.3
Sulfated Ash; wt.%	ASTM D874	wt.%	0.79
Color	VISUAL		Green

Article number 54851
Contents 1 liter

Article number 54855
Contents 5 litres

OCD Nederland BV
Maxwellstraat 41 - 3316GP Dordrecht - Postbus 9024 - 3301 AA Dordrecht
Tel (078) 6512322 - Fax (078) 6174848 - email: support@bardahl.nl - website: www.bardahl.nl

Article number 54882
Contents 25 litres

Article number 54886
Contents 60 litres

Article number 54892
Contents 210 litres

OCD Nederland BV
Maxwellstraat 41 - 3316GP Dordrecht - Postbus 9024 - 3301 AA Dordrecht
Tel (078) 6512322 - Fax (078) 6174848 - email: support@bardahl.nl - website: www.bardahl.nl