

# XTM Motorcycle Oil 15W50 Syntronic

**Bardahl XTM 15W50 Syntronic** has been formulated to meet the increasing stringent requirements of modern motorcycle engines in motorcycles.

**Bardahl XTM 15W50 Syntronic** is a selected mixture of compound hydrocarbons and carefully selected esters. This fully synthetic engine oil has the following properties:

- A high and stable viscosity index
- Optimal friction properties
- A strong anti-wear, anti-corrosion and anti-foaming ability
- A very good deterging and dispersing effect

**Bardahl XTM Syntronic** motorcycle oil contributes to lower fuel consumption (due to reduced friction), lower oil consumption, longer intervals, and longer filter life. This oil is designed to improve emissions and reduce wear and tear for longer engine life. The product has exceptional stability at high temperatures, with perfect lubrication under varying engine loads and in critical ambient temperature applications. It also ensures an easy start at temperatures below zero.

#### **Application**

This engine oil has been specially developed for the lubrication of four-stroke motorcycles, so that the slipping, sticking and /or non-slip shifting of the clutch plates are a thing of the past. This oil has been developed and tested in close cooperation with the main motorcycle manufacturers and has already proven its qualities in practice.

#### **Specifications**

API - SN | JASO - MA2

### **Analysis data**

| Test                        |            |          | Results                            |
|-----------------------------|------------|----------|------------------------------------|
| SAE-class                   | Method     | Unit     | XTM Motorcycle Oil 15W50 Syntronic |
| Viscosity; At 100°C         | ASTM D445  | Cst      | 17.8                               |
| Viscosity; At 40°C          | ASTM D445  | Cst      | 121.30                             |
| Viscosity; cp at-25°C       | ASTM D5293 | mPa.s    | 4600                               |
| Viscosity Index             | ASTM D2270 |          | 168                                |
| Sulphated Ash;              | ASTM D874  | wt.%     |                                    |
| TAN                         | ASTM D664  | mg KOH/g |                                    |
| tbn                         | ASTM D2896 | mg KOH/g | 6.6                                |
| pourpoint                   | ASTM D6892 | °C       | -36                                |
| Color                       | ASTM D1500 |          |                                    |
| Flashpoint                  | ASTM D92   | °C       | 250                                |
| Specific Gravity at 15/15°C | ASTM D4052 | g/ml     | 0.845                              |
| Noack Evaporation;          |            | wt.%     |                                    |

## **PRODUCT INFORMATION**



Article number 55551 Contents 1 liter

Article number 55555 Contents 5 liter

Article number 55582 Contents 25 litres

**Article number** 55586 **Contents** 60 litres

Article number 55592 Contents 210 litres