

## XTC C60 SAE 15W50

**Bardahl XTC C60 SAE 15W50** is a premium engine oil for petrol and diesel engines (with or without turbo) with direct injection

The synthetic bases and the special polymers used in this formula make it possible to achieve extraordinary performance with this engine oil. Even under the toughest conditions, the oil lubricating film holds up and offers resistance to thermal oxidation.

The oil change interval can be extended to the maximum that is allowed by the manufacturer.

The excellent viscosometric properties and the high HTHS value help reduce wear due to viscosity loss at high temperatures.

Thanks to Bardahl technology and the efficiency of the Polar Plus formula With Fullerene, **Bardahl XTC C60 SAE 15W50 enables** a remarkable reduction in friction. In addition, this engine oil contributes to fuel savings and protection of all mechanical parts. Finally, the oil keeps the engine clean and working perfectly and thus contributes to a long service life.

Ideal for sporty driving, where a high viscosity of the oil on requires at high temperatures.

### Properties

---

- Minimal wear due to excellent permanent lubrication film
- Longer service life
- The oil has strong cleaning properties
- Suitable for sporty use, where a high viscosity of the oil is required

### Specifications

---

- API SN-CF
- ACEA A3-B4
- MB 229.1, VW 501.01/505.00

### Analysis data

SAE - Klasse	Test		Results
	Method	Unit	XTC C60 SAE 15W50
Viscosity at 40°C	ASTM D445	cSt	152,6
Viscosity at 100°C	ASTM D445	cSt	19,7
Density at 15°C	ASTM D4052	kg/l	0,876
Viscosità index			149
Flash Point	ASTM D92	°C	200
Pour Point	ASTM D6892	°C	-39
T.B.N.	ASTM D2896	mg KOH/g	9.9

### 15W50

**Article number** 324040

**Content** 1 litre