

XTC 50407 5W30 Syntronic III DPF C3

Bardahl 50407 5W30 Syntronic III DPF C3 is a fuel-saving, universal engine oil, developed according to the latest techniques, based on specially selected base oils, to which advanced additives have been added to obtain the following properties:

- fuel savings
- reduced formation of combustion residues (low SAPS)
- a smooth cold start
- a safe lubricating film at high operating temperatures
- extended drain intervals
- a very good deterrent and dispersing effect
- a very strong anti-wear, anti-corrosion and anti-foaming ability

Application

A universal, fuel-saving, specially formulated engine oil, suitable for petrol, LPG and diesel engines, for which extended drain intervals are possible. This engine oil also contributes to the extension of the life of particulate filters, due to the low SAPS content. Due to its special composition, this product is compatible for the VW 504.00/507.00 standard.

Specifications

ACEA - C2 | ACEA - C3 | API - CF | API - SN | BMW - LONGLIFE-04 | MB - 229.31 | MB - 229.51 | MB - 229.52 | PORSCHE - C30 | VW - 503 01 | VW - 504 00/507 00

Test			Average result
SAE - Classe	Method	Unit	LSP 5W30
Viscosity; mm ² at 100°C	ASTM D445	mm ² at 100°C	11,7
Viscosity; mm ² at 40°C	ASTM D445	mm ² at 40°C	68
Viscosity Index	ASTM D2270		169
Sulfaatas	ASTM D874	Wt%	0.7
Density; 15 °C, kg/l	ASTM D4052	g/ml	0,856
TBN	ASTM D2869	mg KOH/g	8.3
Pourpoint	ASTM D6892	°C	-39
Flashpoint	ASTM D92	°C	230

Article number 53951
Contents 1 liter

Article number 53955
Contents 5 liter

Article number 53982
Contents 25 liter

Article number 53986
Contents 60 liter

Article number 53992
Contents 210 liter