

XTC VFMO Syntronic 0W20 C5

Bardahl XTC VFMO Syntronic 0W20 C5 has been developed to meet the Opel OV0401547 specification. The ultra-low viscosity of this lubricant enables the latest engine designs to achieve their intended fuel efficiency goals. In addition, engine oil forms a strong layer that absorbs harmful particles, keeping the engine clean and providing continuous protection. It is suitable for hybrid vehicles if the OEM specifications are met.

Properties

- Fuel-saving
- Optimal viscosity at low temperatures
- Full protection for loaded engine components

Applications

This engine oil provides complete protection to a range of modern passenger cars and petrol and diesel engines of light trucks, with or without catalytic converter. In addition, it can be used in combination with the latest fuel types, such as ethanol-containing fuels. The API SN Plus specification demonstrates the compatibility of the oil with highly fuel-efficient GDI engines, in which this oil prevents LSPI from damaging various engine components. With **Bardahl XTC VFMO Syntronic 0W20 C5**, some of the most advanced engines can achieve their intended fuel consumption. This is demonstrated by meeting the MB 229.71 and BMW Longlife-17FE+ specifications.

Specifications

- | | |
|-------------------------------------|--|
| — ACEA C5 | — FORD WSS-M2C947-A/ WSS-M2C947-B1 |
| — API SN/Plus | — GM DexosD™ |
| — API SN/RC | — ILSAC GF-5 |
| — ASTON MARTIN | — JAGUAR-LAND ROVER STJLR.03.5006/ STJLR.51.5122 |
| — BMW LONGLIFE-14FE+/LONGLIFE-17FE+ | — MB 229.71 |
| — CHRYSLER MS 12145 | — MITSUBISHI |
| — FIAT 0.55535-GSX | — OPEL OV0401547 |
| — FORD WSS-M2C945-A/WSS-M2C945-B1 | — VOLVO VCC RBS0-2AE |
| — FORD WSS-M2C946-A/ WSS-M2C946-B1 | |

Analysis data

Test			Results
SAE - Class	Method	Unit	0W20 C5
Density , kg/l15 °C	ASTM D4052	g/ml	0.844
Viscosity , mm ² /s 40 °C	ASTM D445	mm ² /s	40.65
Viscosity , mm ² /s100 °C	ASTM D445	mm ² /s	8.08
Viscosity index			176
Pourpoint		°C	-57
Total Base Number		mg KOH/g	7,7
Flashpoint °C		°C	210

Article number 53851

Contents 1 liter

Article number 53855

Contents 5 liter

Article number 53882

Contents 20 liter

Article number 53886

Contents 60 liter

Article number 53892

Contents 210 liter