

# Compressor Oil H68

Bardahl Compressor Oil H68 is an oil intended for the lubrication of air compressors.

## Advantages

---

- Highly refined, paraffinic base oil.
- Excellent thermal stability.
- Exceptional resistance to oxidation.
- Minimal precipitation, this ensures a cleanliness in the entire mechanical part.
- Removes risks such as fire and explosion.
- Excellent corrosion resistance.
- Low evaporation.

## Applications

---

- Air compressors.
- Rotary compressors with oil injection.
- Rotary dry compressors, centrifugal and piston compressors.
- Hydraulic circulation when the manufacturer requests an oil without axle content.

## Specifications

---

DIN - 51506 VDL | PNEUROP - DIN 51.352

## Analysis data

Test			Results
Class ISO	Method	Unit	Compressor Oil H68
Density at 15°C	ASTM D4052	g/ml	0.878
Viscosity 40°C	ASTM D445	mm <sup>2</sup> /s	68
Viscosity 100°C	ASTM D445	mm <sup>2</sup> /s	8,7
Viscosity index	ASTM D2270		101
pourpoint	ASTM D6892	°C	-21
firepoint	ASTM D92	°C	253
TAN	ASTM D974	mg KOH/K	0,12

### Compressor Oil H68

**Article number** 75855

**Contents** 5 litres

**Article number** 75882

**Contents** 25 litres

**Article number** 75886

**Contents** 60 litres

**Article number** 75892

**Contents** 210 litres