



Silicone Spray Lube

Eliminates squeaks - lubricates - protects

Bardahl Silicone Spray Lube is an anti-friction coating for all kind of applications: industrial, in the car, home or office. It will lubricate all plastic, rubber, metal and most moving surfaces.

This product will not wash out, melt or freeze and is quick drying leaving a clean finish.

Bardahl Silicone Spray Lube retards the formation of rust and salt-water corrosion. The clear film is non-staining and will lubricate all sliding parts. The high-quality silicones plus the special penetrating effect, makes this product the ideal clean lubricant and preservative for all rotating and sliding parts. It will repel dirt, sand, dust and water.

Lubricates: car-locks, doors, trunk lids, windows, rubber weather-stripping, speedometer cables etc. Tour, sport, race- and motocross cycles-cables, brake levers, pedals etc., Home & office -sliding doors, drawers, hinges, locks, wooden windows, ski's, runners, zippers etc.

Insulates: car & boat-distributor caps, ignitions, wires, generators, starters and radio antennas against moisture:

Protects: chrome, brass, aluminum, plastic, wood, rubber, vinyl, leather, all kind of sport equipment, garden-tools, seat covers and tire sidewalls.

Eliminates: squeaks caused by friction and rattles or noises under the dashboard. Prevents outside locks from freezing. Stops windows, doors, drawers, hinges, latches, or zippers from sticking. Will not freeze down to -40°C or degrade at +200°C.

Rubber Care: Bardahl Silicone Spray Lube keeps rubber parts smooth and plain. It protects against aging, stickiness and binding at very low temperatures. Parts made of rubber particularly seals on cars and trucks tend to become brittle, sticky or shrink because of aging or the effect of high temperatures.

To extend the life of these components they must be treated with **Bardahl Silicone Spray Lube**, preferably right from the start.

Bardahl Silicone Spray Lube also prevents the freezing of rubber seals around vehicle doors and luggage compartments.



Product information

Directions for use

Apply product directly on to a clean and dry surface; Apply spray from a distance of 30 cm.

NOTE

Bardahl Silicone Spray Lube may be used where contact with food articles can occur (ref: FDA Regulation 21 CFR - 178.3570 or 178.3910). (for more information see our lab report reg. food regulations).

Article number 66304
Contents 400 ml