



100% Silicone Lubricant

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 04/04/2016 Revision date: 15/06/2022 Supersedes version of: 01/06/2021 Version: 1.3

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Name : 100% Silicone Lubricant
UFI : 91AT-T6DA-A00D-V3AT
Product code : 76304
Article number : 76304

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : For professional use only
Consumer uses
Industrial
Function or use category : greases, mineral oils, silicones

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

BARDAHL NL - OCD NEDERLAND BV
Maxwellstraat 41
3316 GP Dordrecht
Nederland
T 0031 78 651 2322 - F 0031 78 617 4848
mjkooijman@bardahl.nl - www.bardahl.nl

1.4. Emergency telephone number

Emergency number : +31 (0) 6 54924171
During office hours: 8.30 t/m 17:00 h

Country	Official advisory body	Address	Emergency number	Comment
	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	0870 243 2241	
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH	0344 892 0111	Only for healthcare professionals
United Kingdom	National Poisons Information Service (Belfast Centre) Royal Victoria Hospital	Grosvenor Road BT12 6BA	0344 892 0111	Only for healthcare professionals

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229
Specific target organ toxicity – Single exposure, Category 3, H336
Narcosis
Hazardous to the aquatic environment – Chronic Hazard, H412
Category 3
Full text of H- and EUH-statements: see section 16

100% Silicone Lubricant

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS02

GHS07

Signal word (CLP)

: Danger

Contains

: pentane

Hazard statements (CLP)

: H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

H336 - May cause drowsiness or dizziness.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, Sources of ignition, open flames. – No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Pressurized container: Do not pierce or burn, even after use.

P260 - Do not breathe vapours, spray, mist.

P271 - Use only outdoors or in a well-ventilated area.

P273 - Avoid release to the environment.

P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P403 - Store in a well-ventilated place.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 - Dispose of contents/container in accordance with local, regional, national and/or international regulation.

P280 - Wear protective gloves, eye protection.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Butane (Note U)(Note C)	CAS-No.: 106-97-8 EC-No.: 203-448-7 REACH-no: 01-2119474691-32	50 – 75	Flam. Gas 1A, H220 Press. Gas (Comp.), H280

100% Silicone Lubricant

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
propane (Note U)	CAS-No.: 74-98-6 EC-No.: 200-827-9 REACH-no: 01-2119486944-21	10 – 25	Flam. Gas 1A, H220 Press. Gas
pentane (Note C)	CAS-No.: 109-66-0 EC-No.: 203-692-4 EC Index-No.: 601-006-00-1 REACH-no: 01-2119459286-30	2.5 – 10	Flam. Liq. 2, H225 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 2, H411
Isobutane	CAS-No.: 75-28-5 EC-No.: 200-857-2 REACH-no: 01-2119485395-27	2.5 – 10	Flam. Gas 1A, H220 Press. Gas (Comp.), H280

Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note U: When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.), Press. Gas (Liq.), Press. Gas (Ref. Liq.), Press. Gas (Diss.). Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Allow affected person to breathe fresh air. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact : No irritant effect.
First-aid measures after eye contact : Ensure adequate flushing of eyes by separating eyelids with the fingers.
First-aid measures after ingestion : Do NOT induce vomiting. Get immediate medical advice and attention.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water haze. Powder. Carbon dioxide. Alcohol resistant foam.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Protection during firefighting : Wear suitable respiratory equipment.

100% Silicone Lubricant

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Keep public away from danger area.

6.1.2. For emergency responders

Protective equipment : Wear proper protective equipment.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Ventilate area. Do not use water for cleaning.

6.4. Reference to other sections

(See section 7: Handling and Storage). For further information refer to section 8: "Exposure controls/personal protection". For disposal of solid materials or residues refer to section 13 : "Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Good ventilation of the workplace required. Do not spray on an open flame or other ignition source. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Container under pressure. Do not drill or burn even after use. Do not expose to temperatures exceeding 50 °C/ 122 °F.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a dry, cool place. Government regulations on storing packagings with pressurized containers must be observed.

Incompatible materials : Direct sunlight. heat.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

propane (74-98-6)

EU - Indicative Occupational Exposure Limit (IOEL)

IOEL TWA [ppm]	1000 ppm
----------------	----------

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

100% Silicone Lubricant

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.1.4. DNEL and PNEC

pentane (109-66-0)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	432 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	3000 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, oral	214 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	643 mg/m ³
Long-term - systemic effects, dermal	214 mg/kg bodyweight/day

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No additional information available

8.2.2. Personal protection equipment

Personal protective equipment:

Gloves. Protective goggles.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Tightly fitting safety goggles

Eye protection			
Type	Field of application	Characteristics	Standard
Safety glasses			EN 166

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Skin and body protection	
Type	Standard
	EN 13034

Hand protection:

Selection of the glove material on consideration of the penetration times, permeability and degradation. Refer to manufacturer's information.

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Solvent-resistant gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	>0.5		EN ISO 374

100% Silicone Lubricant

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Other skin protection

Materials for protective clothing:

Full skin-covering antistatic, chemical and oil resistant clothing and safety shoes are recommended. (EN1149; EN340&EN ISO 13688; EN13034-6).

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Respiratory protection			
Device	Filter type	Condition	Standard
	A2-P2		

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Use suitable disposal containers.

Other information:

Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Ventilate area.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: According to product specification.
Appearance	: Aerosol.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: -44.5 °C
Flammability	: Not available
Explosive properties	: Product is not explosive. Explosive vapour/air mixtures may be formed.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: -97 °C
Auto-ignition temperature	: 285 °C
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Practically not miscible. Organic solvent:91.0%
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: 2100 hPa (20°C)
Vapour pressure at 50°C	: Not available
Density	: 0.585 g/cm³ (20°C)
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Explosion limits : 1.4 – 10.9 vol %

9.2.2. Other safety characteristics

VOC content : 532.3 g/l 91.00%

100% Silicone Lubricant

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Additional information : May form flammable and explosive vapour-air mixture. Not self-igniting

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

No decomposition if used according to specifications.

10.3. Possibility of hazardous reactions

No dangerous reactions known.

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Butane (106-97-8)

LC50 Inhalation - Rat	658 mg/l/4h
-----------------------	-------------

propane (74-98-6)

LC50 Inhalation - Rat	20 mg/l/4h
-----------------------	------------

pentane (109-66-0)

LD50 oral rat	> 2000 mg/kg
---------------	--------------

LC50 Inhalation - Rat	5 mg/l/4h
-----------------------	-----------

Isobutane (75-28-5)

LC50 Inhalation - Rat	> 50 mg/l/4h
-----------------------	--------------

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : May cause drowsiness or dizziness.

pentane (109-66-0)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

STOT-repeated exposure : Not classified
Aspiration hazard : Not classified

100% Silicone Lubricant

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

Butane (106-97-8)

LC50 - Fish [1]	680 mg/l
-----------------	----------

pentane (109-66-0)

LC50 - Other aquatic organisms [1]	4.26 mg/l (Oncorhynchus mykiss 96h)
------------------------------------	-------------------------------------

EC50 - Crustacea [1]	2.7 mg/l
----------------------	----------

EC50 - Other aquatic organisms [1]	10.7 mg/l (Pseudokirchneriella subcapitata)
------------------------------------	---

NOEC (acute)	7.51 mg/l (Pseudokirchneriella subcapitata)
--------------	---

12.2. Persistence and degradability

100% Silicone Lubricant

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

Butane (106-97-8)

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

propane (74-98-6)

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

Isobutane (75-28-5)

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

Butane (106-97-8)

Ecology - soil	If released into the environment, the product will rapidly disperse into the atmosphere where it will undergo photochemical degradation.
----------------	--

propane (74-98-6)

Ecology - soil	If released into the environment, the product will rapidly disperse into the atmosphere where it will undergo photochemical degradation.
----------------	--

Isobutane (75-28-5)

Ecology - soil	If released into the environment, the product will rapidly disperse into the atmosphere where it will undergo photochemical degradation.
----------------	--

12.5. Results of PBT and vPvB assessment

No additional information available

100% Silicone Lubricant

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties : The substance/mixture has no endocrine disrupting properties.

12.7. Other adverse effects

Additional information : Harmful to fishes
Additional information : Endangering to drinking water. Harmful to aquatic organisms. Not in groundwater, surfacewater or sewerage

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Prevent entry to sewers and public waters.

HP Code : HP3 - "Flammable:"
– flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;
– flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;
– flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;
– flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa;
– water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;
– other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.
HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with / / ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
Transport document description				
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS	UN 1950 AEROSOLS
14.3. Transport hazard class(es)				
2.1	2.1	2.1	2.1	2.1
				
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

100% Silicone Lubricant

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207, LP02
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

Transport by sea

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 959
Limited quantities (IMDG)	: SP277
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P207, LP02
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U
Stowage category (IMDG)	: None

Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167
ERG code (IATA)	: 10L

Inland waterway transport

No data available

Rail transport

No data available

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

100% Silicone Lubricant

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

VOC Directive (2004/42)

VOC content : 532.3 g/l 91.00%

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No

SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
	Skin corrosion/irritation - comment	Modified	
	Aspiration hazard - comment	Modified	
	Serious eye damage/irritation - comment	Modified	
	Respiratory or skin sensitisation - comment	Modified	
	STOT-single exposure - comment	Modified	
	Carcinogenicity - comment	Added	
	Germ cell mutagenicity - comment	Added	
	Reproductive toxicity - comment	Added	
	STOT-repeated exposure - comment	Added	
	Acute toxicity - comment	Modified	
	Issue date	Modified	

100% Silicone Lubricant

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Indication of changes			
Section	Changed item	Change	Comments
	Revision date	Modified	
	Supersedes	Modified	
1.1	Other means of identification	Added	
2.2	Precautionary statements (CLP)	Modified	
3	Composition/information on ingredients	Modified	
6.3	Methods for cleaning up	Modified	
6.4	Reference to other sections (8, 13)	Modified	
8.2	Skin and body protection	Modified	
8.2	Eye protection	Modified	
8.2	Hand protection	Modified	
8.2	Other information	Modified	
8.2	Materials for protective clothing	Added	
8.2	Environmental exposure controls	Added	
8.2	Respiratory protection	Modified	
9.2	Additional information	Added	
12.6	Adverse effects on the environment caused by endocrine disrupting properties	Added	

Abbreviations and acronyms:	
	Abbreviations and acronyms: RID: Regulations Concerning the International Transport of Dangerous Goods by Rail ICAO: International Civil Aviation Organization ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonized System of Classification and labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

Full text of H- and EUH-statements:	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Flam. Gas 1A	Flammable gases, Category 1A
Flam. Liq. 2	Flammable liquids, Category 2
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.

100% Silicone Lubricant

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Press. Gas	Gases under pressure
Press. Gas (Comp.)	Gases under pressure : Compressed gas
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.